



φ 8mm

(NTC--Inrush Current Limiting Thermistor)

Part Number	Resistance at 25°C	Tolerance		I _{max}	R _I max.	Thermal dissipation coefficient	Thermal Time constant	Maximum Capacitance AC(μF)	Material constant B(±10%)
	(Ohms)	min	max	(Amps)	(Ω)	(mW/°C)	(sec.)	(240V)	(°K)
JNR08S4R7M	4.7	3.76	5.64	2	0.328	13	42	100	2750
JNR08S040M	4	3.2	4.8	2	0.315	13	42	100	2750
JNR08S050M	5	4	6	2	0.4	16	55	100	2750
JNR08S060L	6	5.1	6.9	2	0.374	16	55	100	2750
JNR08S070L	7	5.95	8.05	2	0.445	16	44	100	2750
JNR08S080L	8	6.8	9.2	2	0.828	16	44	100	2750
JNR08S100L	10	8.5	11.5	2	0.411	16	44	100	2750
JNR08S150L	15	12.75	17.25	2	0.431	12	47	100	2850
JNR08S180L	18	15.3	20.7	2	0.508	12	47	100	2850
JNR08S200L	20	17	23	1	0.529	12	47	100	2850
JNR08S220L	22	18.7	25.3	1	1.424	12	57	100	2850