

CABTITE BP 35MM PA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

Similar to illustration

The blanking plugs are used for the safe closing of unneeded cable passages in the sealing elements.

General ordering data

Version	Blind plug, Cabtite (cable entry system), Polyamide, red, Height: 35 mm, Width: 35 mm, Depth: 35 mm, -60 °C...100 °C, IP66
Order No.	2652480000
Type	CABTITE BP 35MM PA
GTIN (EAN)	4050118662580
Qty.	10 pc(s).

Creation date December 1, 2022 3:32:23 PM CET

Catalogue status 18.11.2022 / We reserve the right to make technical changes.

CABTITE BP 35MM PA

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	35 mm	Depth (inches)	1.378 inch
Height	35 mm	Height (inches)	1.378 inch
Width	35 mm	Width (inches)	1.378 inch
Length	35 mm	Length (inches)	1.378 inch
Diameter	35 mm	Net weight	12.3 g

Temperatures

Operating temperature	-60 °C...100 °C
-----------------------	-----------------

General information

Halogen	No	Material	Polyamide
Outer cable diameter, max.	35 mm	Outer cable diameter, min.	35 mm
Protection degree	IP66	UL 94 flammability rating	V-0

Classifications

ETIM 6.0	EC000879	ETIM 7.0	EC000879
ETIM 8.0	EC000879	ECLASS 9.0	27-14-44-21
ECLASS 9.1	27-14-44-21	ECLASS 10.0	27-14-44-21
ECLASS 11.0	27-14-44-21	ECLASS 12.0	27-14-08-07

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	CAD data – STEP
User Documentation	Cabtite Installation Instructions
Catalogues	Catalogues in PDF-format