

CABTITE BP 28MM PA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

Similar to illustration

The blanking plugs are used for the safe closing of unneeded cable passages in the sealing elements.

General ordering data

Version	Blind plug, Cabtite (cable entry system), Polyamide, red, Height: 30 mm, Width: 28 mm, Depth: 30 mm, -60 °C...100 °C, IP66
Order No.	2652470000
Type	CABTITE BP 28MM PA
GTIN (EAN)	4050118662573
Qty.	25 pc(s).

Creation date December 1, 2022 3:34:55 PM CET

Catalogue status 18.11.2022 / We reserve the right to make technical changes.

CABTITE BP 28MM PA

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	30 mm	Depth (inches)	1.181 inch
Height	30 mm	Height (inches)	1.181 inch
Width	28 mm	Width (inches)	1.102 inch
Length	30 mm	Length (inches)	1.181 inch
Diameter	28 mm	Net weight	3.4 g

Temperatures

Operating temperature	-60 °C...100 °C
-----------------------	-----------------

General information

Halogen	No	Material	Polyamide
Outer cable diameter, max.	28 mm	Outer cable diameter, min.	28 mm
Protection degree	IP66	UL 94 flammability rating	V-0

Classifications

ETIM 6.0	EC000879	ETIM 7.0	EC000879
ETIM 8.0	EC000879	ECLASS 9.0	27-14-44-21
ECLASS 9.1	27-14-44-21	ECLASS 10.0	27-14-44-21
ECLASS 11.0	27-14-44-21	ECLASS 12.0	27-14-08-07

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	CAD data – STEP
Engineering Data	EPLAN
User Documentation	Cabtite Installation Instructions
Catalogues	Catalogues in PDF-format