

**CABTITE BP 21MM PA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Similar to illustration**

Similar to illustration

The blanking plugs are used for the safe closing of unneeded cable passages in the sealing elements.

**General ordering data**

Version	Blind plug, Cabtite (cable entry system), Polyamide, red, Height: 30 mm, Width: 21 mm, Depth: 30 mm, -60 °C...100 °C, IP66
Order No.	<a href="#">2652450000</a>
Type	CABTITE BP 21MM PA
GTIN (EAN)	4050118662559
Qty.	50 pc(s).

Creation date December 1, 2022 3:37:18 PM CET

Catalogue status 18.11.2022 / We reserve the right to make technical changes.

## CABTITE BP 21MM PA

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Dimensions and weights

Depth	30 mm	Depth (inches)	1.181 inch
Height	30 mm	Height (inches)	1.181 inch
Width	21 mm	Width (inches)	0.827 inch
Length	30 mm	Length (inches)	1.181 inch
Diameter	21 mm	Net weight	2.1 g

### Temperatures

Operating temperature	-60 °C...100 °C
-----------------------	-----------------

### General information

Halogen	No	Material	Polyamide
Outer cable diameter, max.	21 mm	Outer cable diameter, min.	21 mm
Protection degree	IP66	UL 94 flammability rating	V-0

### Classifications

ETIM 6.0	EC000879	ETIM 7.0	EC000879
ETIM 8.0	EC000879	ECLASS 9.0	27-14-44-21
ECLASS 9.1	27-14-44-21	ECLASS 10.0	27-14-44-21
ECLASS 11.0	27-14-44-21	ECLASS 12.0	27-14-08-07

### Approvals

ROHS	Conform
------	---------

### Downloads

Engineering Data	<a href="#">CAD data – STEP</a>
Engineering Data	<a href="#">EPLAN</a>
User Documentation	<a href="#">Cabtite Installation Instructions</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>