COAXIAL

Fixed Attenuator

FW-3A+

50Ω Up to 2 W DC to 12000 MHz 3 dB Attenuation

THE BIG DEAL

- Wideband Coverage, DC to 12000 MHz
- Up to 2 Watt Power Handling
- Rugged Unibody Construction
- Off-the-shelf Availability
- Very Low Cost



Generic photo used for illustration purposes only

Model No.	FW-3A+
Case Style	FF704
Connectors	SMA

+RoHS Compliant
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

APPLICATIONS

- Impedance Matching
- Signal Level Adjustment

PRODUCT OVERVIEW

Mini-Circuits' FW-A series are fixed attenuators from DC to 12000 MHz frequency range with excellent flatness in attenuation. FW-A series is available with nominal attenuation of 1 to 20 dB. This attenuator series support testing and measurement application. Precise performance, excellent VSWR and rugged unibody construction makes the model ideal solution for systems requiring precise attenuation across very wide frequency range.

KEY FEATURES

Feature	Advantages
Rugged Construction	Excellent durability for a long lifetime of use
Up to 2 Watt Power Handling	Good power handling
Excellent VSWR	Well-matched for 50 Ω systems
Flat Attenuation	Improved system calibration and repeatability

REV. C
ECO-029367
FW-3A+
EDU4292
MCINU
260427

COAXIAL

Fixed Attenuator

FW-3A+


50Ω Up to 2 W DC to 12000 MHz 3 dB Attenuation

MAXIMUM RATINGS

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C

Permanent damage may occur if any of these limits are exceeded.

OUTLINE DRAWING




OUTLINE DIMENSIONS (Inch / mm)

B	D	E	wt
.410	1.43	.312	grams
10.41	36.32	7.92	10.0

Note: Please refer to case style drawing for details

ELECTRICAL SCHEMATIC




ELECTRICAL SPECIFICATIONS AT 25°C


Parameter	Condition (MHz)	Min.	Typ.	Max.	Unit
Frequency Range		DC	-	12000	MHz
Attenuation[1]	10	-	3	-	dB
	DC - 3000	2.7	3.15	3.3	
	3000 - 8000	2.7	3.2	3.6	
	8000 - 12000	3.0	3.4	4.0	
VSWR	DC - 3000	-	1.10	1.50	:1
	3000 - 8000	-	1.15	1.55	
	8000 - 12000	-	1.25	-	
Input Power[2]	DC - 12000	-	-	2.0	W

1. Attenuation varies by 0.3 dB max. over temperature.
2. Maximum RF power at 25°C is 2.0 W; Derate linearly to 1.0 W at 85°C

TYPICAL PERFORMANCE DATA

Frequency (MHz)	Attenuation (dB)	VSWR (:1)
10	2.92	1.13
100	2.94	1.14
500	2.98	1.13
1000	3.02	1.13
2000	3.08	1.13
3000	3.11	1.13
5000	3.16	1.13
6000	3.20	1.14
8000	3.28	1.08
9000	3.31	1.10
9500	3.34	1.13
10000	3.36	1.17
10500	3.38	1.19
11000	3.39	1.20
12000	3.41	1.17





NOTES

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard. Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp