CERAMIC


Band Pass Filter

BFCN-2500+

50Ω 2100 to 2900 MHz

THE BIG DEAL

- Small Size, 3.2 × 1.6 mm
- Good VSWR, 1.8:1 typ. at Passband
- Temperature Stable
- LTCC Construction



Generic photo used for illustration purposes only

CASE STYLE: FV1206-4

+RoHS Compliant
The +Suffix identifies RoHS Compliance.
See our website for methodologies and qualifications

APPLICATIONS

- Harmonic Rejection
- Transmitters/Receivers

PRODUCT OVERVIEW

The BFCN-2500+ LTCC band pass filter covers the 2100 to 2900 MHz passband with 2 dB passband insertion loss and 20 dB upper/lower stopband rejection. This model handles up to 2.5 W RF input power and provides a wide operating temperature range from -55 to +100 °C. Utilizing LTCC multi-layer construction, the filter achieves excellent repeatability of performance and comes in a tiny 1206 ceramic package with wraparound terminations, minimizing performance variations due to parasitics and saving space in dense PCB layouts.

KEY FEATURES

Features	Advantages
Small Size, 3.2 × 1.6 mm	Saves space in dense circuit boards and minimizes the effects of parasitics.
LTCC Construction	Provides a rugged package well suited for tough environments such as high humidity and temperature extremes.
Wrap-Around Terminations	Provides excellent solderability and easy visual inspection.
Wide Operating Temperature Range, -55 to +100 °C	Enables reliable performance in extreme environments.

REV. D
ECO-031453
BFCN-2500+
MCL NY
261006

Band Pass Filter

BFCN-2500+

50Ω 2100 to 2900 MHz

ELECTRICAL SPECIFICATIONS[1,2] AT +25 °C

Parameter		F#	Frequency (MHz)	Min.	Typ.	Max.	Units
Passband	Center Frequency	-	-	-	2500	-	MHz
	Insertion Loss	F1–F2	2100–2900	-	2	3.7	dB
	VSWR	F1–F2	2100–2900	-	1.8	2.6	:1
Stop Band, Lower	Insertion Loss	DC–F3	1600	-	20	-	dB
	VSWR	DC–F3	1600	-	20	-	:1
Stop Band, Upper	Insertion Loss	F4–F5	3700–5200	-	20	-	dB
	VSWR	F4–F5	3700–5200	-	15	-	:1


1. Measured on Mini-Circuits Characterization Test Board TB-BFCN-2500+.
2. This filter is not intended for use as a DC blocking circuit element. In applications where DC voltage is present at either input or output ports, blocking capacitors are required at the corresponding RF port.

ABSOLUTE MAXIMUM RATINGS

Parameter	Ratings
Operating Temperature	-55 °C to +100 °C
Storage Temperature	-55 °C to +100 °C
RF Power Input[3]	2.5 W at 25 °C

3. Passband rating, derate linearly to 0.7 W at +100 °C ambient
Permanent damage may occur if any of these limits are exceeded.

TYPICAL FREQUENCY RESPONSE




CERAMIC

Band Pass Filter

BFCN-2500+

50Ω 2100 to 2900 MHz

FUNCTIONAL SCHEMATIC




PAD CONNECTIONS

RF IN	1
RF OUT	3
GROUND	2,4

PRODUCT MARKING: MW

DEMO BOARD P/N: TB-BFCN-2500+

SUGGESTED PCB LAYOUT (PL-454)




NOTES:
1. TRACE WIDTH PARAMETERS ARE SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .0066"±.0007". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.


DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER).

DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK.

CASE STYLE DRAWING



PCB Land Pattern



Suggested Layout,
Tolerance to be within ±.002

OUTLINE DIMENSIONS (Inches / mm)

A	B	C	D	E	F	G	H	J
.126	.063	.037	.026	.075	.012	.182	.104	.069
3.20	1.60	0.94	0.66	1.91	0.30	4.62	2.64	1.75

K	L	M	N	P	Q	R		wt
.119	.041	.039	.013	.024	.020	.039		grams
3.02	1.04	0.99	0.33	0.61	0.51	0.99		.020

TAPE & REEL INFORMATION: F75

CERAMIC

Band Pass Filter


BFCN-2500+

50Ω 2100 to 2900 MHz


TYPICAL PERFORMANCE DATA AT +25 °C

Full Band Performance			Pass Band Performance		
Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)	Frequency (MHz)	Insertion Loss (dB)	Group Delay (nsec)
10	58.18	79.99	2100	1.88	0.90
40	84.01	78.80	2150	1.70	0.81
100	69.04	74.42	2200	1.63	0.73
400	45.88	61.11	2250	1.60	0.66
1000	34.16	43.74	2300	1.60	0.62
1500	33.62	29.10	2320	1.60	0.59
2100	1.88	1.20	2340	1.60	0.58
2500	1.65	1.53	2360	1.61	0.57
2900	2.41	2.16	2380	1.61	0.57
3400	4.69	1.76	2400	1.62	0.56
3800	27.88	14.98	2500	1.65	0.55
4200	39.01	20.59	2600	1.74	0.54
4600	33.90	20.73	2700	1.89	0.54
5000	42.09	11.56	2800	2.11	0.54
5200	28.75	6.04	2900	2.41	0.55


INSERTION LOSS (Full Band)




INSERTION LOSS (Pass Band)



VSWR



GROUP DELAY



NOTES

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/terms/viewterm.html